






ULTRA Anchor Selection Table

RECOMMENDED ULTRA ANCHOR WEIGHT	SAIL BOAT			POWER BOAT			MULTIHULL		
	 MONO HULL								
	Boat Weight	Boat Length		Boat Weight	Boat Length	Boat Length	Boat Weight	Boat Length	Boat Length
(kg) / (lbs)	(ton) (lbs)	(m) (feet)	(ton) (lbs)	(m) (feet)	(m) (feet)	(ton) (lbs)	(m) (feet)	(m) (feet)	
UA 5/11	1 - 2 205	5 - 17	1,1 - 2 425	5,2 - 17	5,7 - 19	0,7 - 1 543	4,3 - 14	4,6 - 15	
UA 8/18	2 - 4 410	7 - 23	2,2 - 4 850	7,2 - 24	7,9 - 26	1,4 - 3 086	6,1 - 20	6,4 - 21	
UA 12/26	3,8 - 8 380	9 - 30	4,2 - 9 260	9,3 - 31	10,2 - 33	2,7 - 5 950	7,8 - 26	8,2 - 27	
UA 16/35	6,3 - 13 890	10,8 - 35	6,9 - 15 210	11,1 - 36	12,2 - 40	4,5 - 9 920	9,3 - 31	9,8 - 32	
UA 21/46	10,2 - 22 490	12,6 - 41	11,2 - 24 690	13 - 43	14,3 - 47	7,3 - 16 100	10,9 - 36	11,5 - 38	
UA 27/60	14,6 - 32 190	14,3 - 47	16 - 35 270	14,7 - 48	16,2 - 53	10,5 - 23 150	12,4 - 41	13 - 43	
UA 35/77	21,5 - 47 400	16 - 52	23,5 - 51 800	16,5 - 54	18,2 - 60	15,6 - 34 400	13,8 - 45	14,6 - 48	
UA 45/100	30 - 66 140	17,8 - 58	32,9 - 72 530	18,3 - 60	20,1 - 66	21,6 - 47 620	15,4 - 51	16,2 - 53	
UA 60/132	43 - 94 800	20 - 66	47,1 - 103 830	20,6 - 68	22,7 - 74	31 - 68 340	17,3 - 58	18,2 - 60	
UA 80/176	63 - 139 880	22,3 - 73	69 - 152 120	23 - 75	25,3 - 83	45,4 - 100 100	19,3 - 63	20,3 - 67	
UA 100/220	85 - 187 000	24,5 - 80	93 - 205 000	25,2 - 83	27,7 - 91	61 - 134 000	21,2 - 70	22,3 - 73	
UA 130/290	123 - 271 000	27,4 - 90	135 - 298 000	28,2 - 93	31 - 102	89 - 196 000	23,7 - 78	25 - 82	
UA 160/350	174 - 384 000	30,4 - 100	191 - 421 000	31,3 - 103	34,4 - 113	125 - 276 000	26,3 - 86	27,7 - 91	
UA 200/440	262 - 578 000	34,4 - 113	287 - 630 000	35,4 - 116	39 - 128	190 - 419 000	29,8 - 98	31,3 - 103	
UA 250/550	400 - 882 000	39,2 - 129	438 - 966 000	40,4 - 133	44,4 - 146	290 - 639 000	33,9 - 111	35,7 - 117	
UA 300/660	550 - 1 213 000	44 - 144	600 - 1 323 000	45,3 - 149	49,8 - 163	400 - 882 000	38,1 - 125	40 - 131	
UA 360/800	760 - 1 675 000	50 - 164	830 - 1 830 000	51,5 - 169	56,7 - 186	550 - 1 213 000	43,3 - 142	45,5 - 150	

COMMENTS:

- When Selecting ULTRA Anchors in excess of 100Kg/220lbs, please consult Lloyd's or a comparable certification society's guidelines. The listed values should be used for preliminary selection only.

- ULTRA Anchors work well as bow and stern anchors on horizontal roller assemblies. They are not suitable for vertical or straight hawse pipes.

- If choosing the anchor for a boat that is very light or very heavy, first identify the row that matches the weight of the boat, then:
 • For lighter boats, choose 1 size bigger
 • For heavier boats, choose 1 size smaller.

WARRANTY:

- Properly selected or one size smaller ULTRA Anchors are covered by our lifetime warranty against issues arising from production or normal use.

- However, anchors that are two or more sizes smaller than recommended are not covered under warranty.

CAUTION:

- The ULTRA Anchor is designed to handle extreme heavy loads and caution is advised when handling.

- All materials have resistance limits. The use of high powered engines to free an anchor may deform it and/or cause damage to the vessel.

- It is recommended to use a trip line or an ULTRA Anchor Ring to recover an anchor stuck and an obstruction.

We reserve the right to make changes to dimensions and conditions.

This document was updated on the 08.11.2024

For the latest version, please visit www.ultraproductswest.com