






ULTRA Side Pocket Anchor Selection Table

RECOMMENDED ULTRA SIDE POCKET ANCHOR WEIGHT	SAIL BOAT			POWER BOAT			MULTIHULL		
	 MONO HULL			 HIGH PROFILE		 LOW PROFILE	 SAIL		 POWER
	Boat Weight	Boat Length		Boat Weight	Boat Length	Boat Length	Boat Weight	Boat Length	Boat Length
(kg) / (lbs)	(ton) (lbs)	(m) (feet)	(ton) (lbs)	(m) (feet)	(m) (feet)	(ton) (lbs)	(m) (feet)	(m) (feet)	
21/46	6,3 - 13 890	10,8 - 35	6,9 - 15 210	11,1 - 36	12,2 - 40	4,5 - 9 920	9,3 - 31	9,8 - 32	
27/60	10,2 - 22 490	12,6 - 41	11,2 - 24 690	13 - 43	14,3 - 47	7,3 - 16 100	10,9 - 36	11,5 - 38	
35/77	14,6 - 32 190	14,3 - 47	16 - 35 270	14,7 - 48	16,2 - 53	10,5 - 23 150	12,4 - 41	13 - 43	
45/100	21,5 - 47 400	16 - 52	23,5 - 51 800	16,5 - 54	18,2 - 60	15,6 - 34 400	13,8 - 45	14,6 - 48	
60/132	30 - 66 140	17,8 - 58	32,9 - 72 530	18,3 - 60	20,1 - 66	21,6 - 47 620	15,4 - 51	16,2 - 53	
80/176	43 - 94 800	20 - 66	47,1 - 103 830	20,6 - 68	22,7 - 74	31 - 68 340	17,3 - 58	18,2 - 60	
100/220	63 - 139 880	22,3 - 73	69 - 152 120	23 - 75	25,3 - 83	45,4 - 100 100	19,3 - 63	20,3 - 67	
130/290	85 - 187 000	24,5 - 80	93 - 205 000	25,2 - 83	27,7 - 91	61 - 134 000	21,2 - 70	22,3 - 73	
160/350	123 - 271 000	27,4 - 90	135 - 298 000	28,2 - 93	31 - 102	89 - 196 000	23,7 - 78	25 - 82	
200/440	174 - 384 000	30,4 - 100	191 - 421 000	31,3 - 103	34,4 - 113	125 - 276 000	26,3 - 86	27,7 - 91	
250/550	262 - 578 000	34,4 - 113	287 - 630 000	35,4 - 116	39 - 128	190 - 419 000	29,8 - 98	31,3 - 103	
300/660	400 - 882 000	39,2 - 129	438 - 966 000	40,4 - 133	44,4 - 146	290 - 639 000	33,9 - 111	35,7 - 117	
360/800	550 - 1 213 000	44 - 144	600 - 1 323 000	45,3 - 149	49,8 - 163	400 - 882 000	38,1 - 125	40 - 131	
420/925	760 - 1 675 000	50 - 164	830 - 1 830 000	51,5 - 169	56,7 - 186	550 - 1 213 000	43,3 - 142	45,5 - 150	
500/1100	100 - 2 204 600	55 - 180	1100 - 2 425 000	59 - 193	64 - 210	750 - 1 653 000	49 - 161	51 - 167	

COMMENTS:

- When Selecting ULTRA Anchors in excess of 500Kg/1100lbs, please consult Lloyd's or a comparable certification society's guidelines. The listed values should be used for preliminary selection only.

- If used in a side pocket setup, the anchor must be "Balanced".

- If used in a bow setup, the anchor should be "Unbalanced".

- This table applies to all Ultra Side Pocket Anchors, both Standard and Compact.

WARRANTY:

- Properly selected ULTRA Side Pocket Anchors are covered by our lifetime warranty against issues arising from production or normal use.

CAUTION:

- The ULTRA Side Pocket Anchor is designed to handle extreme heavy loads and caution is advised when handling.

- All materials have resistance limits. The use of high powered engines to free an anchor may deform it and/or cause damage to the vessel.

- It is recommended to use a trip line to recover an anchor stuck under an obstruction.

We reserve the right to make changes to dimensions and conditions.

This document was updated on the 17.04.2026

For the latest version, please visit www.ultraproductswest.com

